## Safety Data Sheet

Revision Date: May 15, 2015 Revision Number: Issuing Date: May 15, 2015

1. Identification of the Substance/Preparation and the Company Undertaking

#### **GHS Product Identifier**

**Product Name** MPD-X, All colors

#### Other Means of Identification

Part Number: 00120 (Black), 00220 (Blue), 00320 (Brown), 00420 (Gold), 00520 (Green), 00620 (Light Blue), 00720 (Light Green), 00820 (Orange), 00920 (Purple), 01020 (Pink), 01120 (Red), 01220 (Silver), 01320 (White), 01420 (Yellow)

Formula Code: Black: XV-585, Blue: XV-11753, Brown: XV-12578, Gold: XV-654, Green: XV-11724, Light Blue: XV-11802, Light Green: XV-478, Orange: XV-12491, Purple: XV-671, Pink: XV-12081, Red: XV-543, Silver: XV-642, White: XV-11719, Yellow: XV-11619, Violet: XV-12574

**Synonyms** none

## Recommended use of the chemical and restrictions on use

**Recommended Use** Marker

**Uses Advised Against** No information available

## Supplier's Details

#### **Supplier Address**

Marking Pen Depot 41775 Elm Street, Unit 403 Murrietta, CA 92562 USA Phone: (888) 396-3848

## **Emergency Telephone Number**

Chemtrec International 703-527-3887 US 800-424-9300

#### 2. HAZARD IDENTIFICATION

#### Classification

This chemical is considered hazardous according to the OSHA Hazard Communications Standard 2012 (29 CFR 1910.1200)

Flammable Liquid Category 3

Skin Corrosion/Irritation Category 2

Serious eye damage/Eye Irritation Category

2A Acute Toxicity Inhalation Category 4

Acute Toxicity Skin Category 4

Aspiration Hazard Category 1

Carcinogenicity Inhalation

Category 2

Specific target Organ Toxicity (single Exposure) respiratory tract irritation Category 3

Specific target Organ Toxicity (repeated Exposure) Inhalation Category 2

## GHS Label Elements, including precautionary statements

#### Signal Word - Danger

Causes skin irritation.

Causes serious eye

irritation.

May cause respiratory irritation.

Harmful if inhaled.

Harmful in contact with

skin.

May be fatal if swallowed and enters airways.

May cause damage to organs through prolonged or repeated exposure by inhalation.

Suspected of causing cancer if inhaled.

Flammable liquid and

vapor.







**Appearance** – Opaque, varies **Physical state**- Thin viscosity liquid **Odor** – Aromatic Odor

# Precautionary Statements Prevention

Do not handle until all safety precautions have been read and understood Obtain special instructions before use Keep container tightly closed Use only in a well ventilated

area

Do not breathe dust/vapors/fumes

Wash face and hands and any exposed skin thoroughly after handling

Wear protective gloves/clothing/eye protection/face protection

Keep away from heat/sparks/flame hot surfaces – no smoking

Use explosion proof electrical/ventilating/lighting equipment

Ground/bond container and receiving equipment.

Use non sparking tools

Take precautionary measures against static discharge

#### Response:

If exposed or concerned: get medical attention/advice.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

If swallowed: Immediately call a poison center/doctor. Do not induce vomiting. In case of fire: Use CO2, dry chemical, foam or water spray to extinguish.

#### Storage:

Store in a well-ventilated place.

Keep cool.

Store locked up.

Keep container tightly closed.

#### **Disposal**

Dispose of contents/container in approved waste disposal plant.

#### **General Advice**

If exposed or concerned: get medical attention/advice

ACUTE HAZARD: At high concentration, dizziness and unconsciousness may occur.

CAUTION: Contains xylene. Harmful or fatal if swallowed. Avoid inhalation. Direct contact may cause skin or eye irritation.

KEEP OUT OF REACH OF CHILDREN.

#### **Fire**

Use CO2, dry chemical, foam, or water spray

#### Spills and Leaks

Contain and collect spillage

## **Hazard not Otherwise Classified (HNOC)**

Not applicable

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS -No	Weight %	Trade Secret
Xylene	1330-20-7	10-40	*
Titanium Dioxide	13463-67-7	10-40	*
Resin	proprietary	5-40	*
Colorant	proprietary	1-10	*

<sup>\*</sup> The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. FIRST AID MEASURES

#### Description of necessary first-aid measures

**General Advice** In case of doubt, or when symptoms persist, seek medical attention.

Eye Contact minutes.

Immediately flush eyes with plenty of water for at least fifteen (15)

Get medical attention immediately.

**Skin Contact** Flush skin with plenty of water. Remove contaminated clothing.

Was skin thoroughly with soap and water or use a proprietary skin

Page 3.

cleanser.

**Inhalation:** Remove to fresh air, keep patient warm and at rest. If breathing is

irregular seek medical advice. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention

immediately.

**Ingestion** Seek medical attention immediately. Do not induce vomiting.

Never give anything by mouth to an unconscious person.

Protection of First Aiders Use personal protection equipment.

#### Most important symptoms/effects, acute and delayed

Most important symptoms/effects No information available

## Indication of immediate medical attention and special treatment needed, if necessary

Note to physician Treat symptomatically

#### 5. FIRE-FIGHTING MEASURES

#### Suitable Extinguishing Media

Dry chemical, carbon dioxide, regular foam. For large fires, use foam or flood with fine water spray

Unsuitable extinguishing media No information available

## Specific Hazards arising from the chemical No information available

Flash Point: 70°F

Flammability Limits (% by volume): Lower -1.1%; Upper -6.4%

Unusual Fire Explosion Hazards: none

## **Protective Equipment and Precautions for Firefighters**

Wear appropriate self-contained breathing apparatus MSHA/NIOSH (approved or equivalent) and full protective gear. Cool closed containers exposed to fire with water spray. Avoid inhalation of material or combustion by-products; stay upwind.

## **6. ACCIDENTAL RELEASE MEASURES**

## Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Avoid breathing vapours. Evacuate personnel to safe areas. Ensure

adequate ventilation.

Environmental Precautions Avoid release into the environment. Do not allow to enter drains or

watercourses.

#### Methods and materials for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for Cleaning Up** Contain the spillage with non-combustible absorbent materials

such as sand, earth, vermiculite, diatomaceous earth to soak up the product and place in a suitable container for disposal in

accordance with the waste regulations

## 7. HANDLING AND STORAGE

## Precautions for safe handling

**Handling** Avoid skin and eye contact. Avoid the inhalation of vapor and mist.

#### Conditions for safe storage, including any incompatibilities

**Storage** Keep away for open flame, hot surfaces and sources of ignition.

Keep containers tightly closed. Observe label precautions. Store

between 5-25° C in a dry, well ventilated place. Prevent

unauthorized access.

Incompatible products Unknown

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control Parameters**

## **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Titanium Dioxide 13463-	TWA 10 mg/m3	TWA 15 mg/m3 total dust	IDHL 5000 mg.m3
67-7		Vacated TWA 5 mg/m3 total dust	
Xylene 1330-20-7	STEL 150 ppm	TWA 100 ppm	
	TWL 100 ppm	TWA 435mg/m3	-
		Vacated TWA 100 ppm	
		Vacated TWA 435 mg/m3	
		Vacated STEL 150 ppm	
		Vacated STEL 655 mg/m3	

## Appropriate engineering controls

**Engineering Measures** Showers, eyewash stations, ventilation systems

#### Individual protection measures, such as personal protective equipment

**Eye/Face protection** None under normal use conditions

Skin and body Protection None under normal use conditions

**Respiratory Protection** None under normal use conditions. If irritation is experienced,

NIOSH/MSHA approved respiratory protection should be worn

**Hygiene Measures** Use in a well-ventilated area. When using do not eat, drink, or smoke.

Provide regular cleaning of equipment, work areas and clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

<u>Property</u> <u>Value</u>

Boiling Point: 282 to 286°F

Specific Gravity (H20=1) @70°F: >1
Vapor Pressure (mm-Hg @ 70°F): No Data
Melting Point: No Data
Vapor Density (AIR = 1): Greater than
one (1) Evaporation Rate (Butyl Acetate = 1): Less than one
(1) Solubility in Water: Negligible

Page 5.

PH: No Data

Appearance and Odor: Opaque, thin viscosity liquid with aromatic odor.

Volatile Organic Compound: 705 grams per liter

## 10. STABILITY AND REACTIVITY

Reactivity No data available

Chemical Stability Stable under normal storage and handling conditions

Possibility of Hazardous reactions None under normal use

Hazardous Polymerization Will not occur

Conditions to Avoid Heat, open flame, sparks, and sources of ignition

Incompatible Materials Strong oxidizing and reducing agents, strong

alkalis and strong acids

**Hazardous Decomposition - products** 

various

Carbon dioxide, carbon monoxide, smoke, soot and

oxidation by-products.

#### 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

**Product Information** There is no data available on the product itself.

Chemical	LD50 oral	LD50 Dermal	LD50 Inhalation
Xylene	3500 mg/kg rat	4350 mg/kg rabbit	29.08 mg/l rat
Titanium dioxide	1000 mg/kg rat	-	-

## 12. ECOLOGICAL INFORMATION

**Ecotoxity** There is no data available on the product itself

## 13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with all applicable local, state and federal

regulations.

**Contaminated Packaging** Do not re-use empty containers.

#### 14. TRANSPORT INFORMATION

## Domestic Highway (Containers <1 Quart are ORM-D) Proper Shipping Name:

Consumer Commodity

Hazard Class/Subsidiary: ORM-D UN/NA No.: None Packing Group: None Label Required: ORM-D

## 15. REGULATORY INFORMATION

TSCA INVENTORY: The product on this SDS is not listed on the Toxic Substances Control Act Inventory. All ingredients used to manufacture this product are listed on the TSCA Inventory.

## **US Regulatory Rules:**

Section 313 or Title III of SARA. This product contains a chemical which is subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations Part 372.

Titanium Dioxide 13463-67-7

Xylene 1330-20-7

SARA 311-312 Hazard categories Acute Health Hazard

YES Chronic Health Hazard

YES Fire Hazard

YES

Sudden release of Pressure Hazard NO Reactive Hazard NO

California Proposition 65 Titanium Dioxide 13463-67-7 carcinogen MA Right to know List New Jersey Right to Know Xylene 1330-20-7 Listed Pennsylvania Right to Know Xylene 1330-20-7

Listed

## **16. OTHER INFORMATION**

Health Hazard 2 Flammability 3 Reactivity 0 Personal Protection

В

## **End of Safety Data Sheet**